

INTEGRAPLY™

ENGINEERED UNDERLAYMENT



25-YEAR LIMITED WARRANTY

100% ENGINEERED

EXTERIOR GLUE (LFE)

RECOMMENDED UNDERLAYMENT

*RECOMMENDED BY THE MAJOR FLOORING
MANUFACTURERS*

IntegraPly™ Underlayment Specifications

Characteristics:

Uniform light rotary cut face
5.5mm thickness -0.3mm; +0.0mm
5 Ply core...minimal voids
Clear face...minimal defects or repairs
Fully sanded face and back

Grades:

Sound sanded face
Sanded to uniform thickness

Glues:

Low Formaldehyde Emission (LFE), exterior glue which meets or exceeds the
Hardwood Plywood Veneer Association (HPVA)
standards for LFE exterior glue.

Markings:

Each sheet will have light color "Xs" stamped on the face of each sheet indicating
the recommended nailing pattern.
All "Xs" are distributed uniformly every 4" inches.
All "Xs" are printed to not add any thickness to the sheet, eliminating telegraphing
or risk of visibility through thinner vinyl flooring.

Dimensions:

1/4" (5.5mm) - 48" x 96"
All sheets are square within 3/16" as to length and width.
(within HPVA standards)



Russ McCall, President
Integra Wood International

***Successfully tested by the Tile
Council of North America for use
under ceramic tile, including
"heavy duty and high-impact"***



July 16, 2008

Integra Wood
474 Wando Park Blvd., Suite 205
Mt. Pleasant, SC 29464
Attn: Russ McCall

Re: IntegraPly™ Underlayment

Dear Mr. McCall:

We have completed the testing of the Integra Wood IntegraPly Underlayment and Tarkett Resilient Sheet Flooring. The testing was performed using Tarkett felt backed and PVC foam backed sheet flooring and the recommended adhesives. The test results showed satisfactory adhesion properties with your product. Based on the test results, Tarkett will include IntegraPly as a recommended underlayment panel for use under Tarkett Residential Sheet Flooring.

Please be advised that Tarkett does not guarantee or warrant underlayment panels used with Tarkett flooring. All guarantees and/or warranties are the responsibility of the panel manufacturer, not Tarkett.

Best regards,


Kelly Pitts
Technical Service Department